

Raspbian 10

Prepare SD card

- Download and install the [RaspBerry Pi Imager](#)
- Copy “RaspBerryPi OS Lite” to the SD card

Install OS

- Boot from SD card
- Update all packages
- Enable SSH server in *Interface Options* and set location and keyboard in *Localisation Options*:

```
sudo raspi-config
```

- Change host name
- Config [SSH](#) and generate SSH keys
- Exchange public key files
- Install missing packets:

```
apt install autossh vim
```

Install AutoSSH

Install AutoSSH on a **remote_host** to connect to my main server (**local_host**) to allow connections from **any_host** (either at the local location, or at any other remote location) back to the remote host.

Remote location

1. Verify access from local_host and any_host: SSH from **remote_host** to **local_host**:<ssh_port_local_host> with key pair authentication and establish tunnel, requires <ssh_port_local_host> to be open on local location:

```
remote_host$ ssh -R <port_to_access_remote_from_local>:localhost:22  
user@<domain_name_of_local_host> -p <ssh_port_local_host>
```

2. Once confirmed, create file *autossh-tunnel.service* in */etc/systemd/system/*:

```
[Unit]  
Description=AutoSSH tunnel service Remote port  
<port_to_access_remote_from_local> to local 22  
After=network.target  
  
[Service]
```

```
Environment="AUTOSSH_GATETIME=0"  
ExecStart=/usr/bin/autossh -o "ServerAliveInterval 10" -o  
"ServerAliveCountMax 3" -N -R  
<port_to_access_remote_from_local>:localhost:22  
user@<domain_name_of_local_host> -p <ssh_port_local_host> -i  
/home/pi/.ssh/id_ecdsa
```

```
[Install]  
WantedBy=multi-user.target
```

We need to tell SSH the identity file as systemd will run as root. The environment variable is added so the autossh service can run in the background.

3. Once we have the service file created start the service and enable it to run at boot:

```
remote_host$ sudo systemctl daemon-reload  
remote_host$ sudo systemctl start autossh-tunnel.service  
remote_host$ sudo systemctl enable autossh-tunnel.service
```

Local location

1. Verify: SSH from **local_host** to **remote_host** through tunnel at
<port_to_access_remote_from_local>

```
local_host$ ssh pi@localhost -p <port_to_access_remote_from_local>
```

Any location

1. Verify: SSH to **local_host** and establish tunnel from (any_host)
<port_to_access_remote_from_local> to localhost:<port_to_access_remote_from_local>
2. Verify: SSH from any_host to localhost:<port_to_access_remote_from_local>

Links

- [SSH tunneling with Autossh](#)

From:
<https://wiki.condrau.com/> - **Bernard's Wiki**

Permanent link:
<https://wiki.condrau.com/deb10:raspi?rev=1619523368>

Last update: **2021/04/27 18:36**

