phpMyAdmin

Debian 10/11, other than Debian 9, require manual installation of phpmyadmin, phpmyadmin has been removed from Debian's repositories.

Installation

1. Download the latest phpMyAdmin from the Downloads page, scroll down to the table with download links for the latest stable release, and copy the download link ending in tar.gz:

```
$ wget
https://files.phpmyadmin.net/phpMyAdmin/5.2.0/phpMyAdmin-5.2.0-english.
tar.gz
```

2. Unzip the tarball, then move the folder to a local folder outside of apache's document root (we will create a path alias in phpMyAdmin's `apache.conf` later) and set ownership:

```
$ tar xvf phpMyAdmin-5.2.0-english.tar.gz
sudo mv phpMyAdmin-5.2.0-english/ /home/user/html/phpMyAdmin
$ sudo chown -R www-data:www-data /home/user/html/phpMyAdmin
```

- Up to Debian 9, and in other distributions, phpMyAdmin could be installed via the package manager. Debian 10 dropped the support through the package manager.

Configuration

1. We will not use any of the standard path used in Debian versions up to 9 or in other distributions. All files related to phpMyAdmin will remain in the custom path where we moved the downloaded files which is the easiest way to later maintain (`/home/user/html/phpMyAdmin`).
2. Make a new directory for phpMyAdmin to store its temporary files:

```
sudo mkdir -m770 /home/user/html/phpMyAdmin/tmp
```

3. Copy `config.sample.inc.php` to `config.inc.php` and edit as follows
    1. Use the phpMyAdmin blowfish secret generator to create a new secret passphrase for cookie authentication:

```
$ sudo vim /home/user/html/phpMyAdmin/config.inc.php
$cfg['blowfish_secret'] = 'new 32 byte secret key';
```

    2. Add the following custom settings to `config.inc.php`:

```
$cfg['FirstLevelNavigationItems'] = 150;// number of databases in
navigation, default: 100
$cfg['MaxNavigationItems'] = 150; // number of tables in db
```

```
navigation, default: 50
$cfg['NavigationWidth'] = 300;        // width of the navigation
window, default: 240
$cfg['RetainQueryBox'] = true;        // retain query box, results
of query shown below box, default: false
$cfg['ShowPhpInfo'] = true;       // show phpinfo link on home
screen, default: false
```

4. You may check phpMyAdmin's documentation for other settings to add
5. Leave the commented out settings in `config.inc.php` unchanged. The pma settings are better done within phpMyAdmin, where you click "Find out why" in the warning at the bottom of the screen when you first run phpMyAdmin, and then create the database `phpmyadmin` which will contain those settings.

- Copy folder phpmyadmin from a Debian 9 installation to /etc. Check the **apache.conf** file and remove path elements in *php_admin_value open_basedir* which do not exist in your system.
- Symlink the configuration files for apache:

```
cd /etc/apache2/conf-available
ln -s ../../phpmyadmin/apache.conf phpmyadmin.conf
cd ../conf-enabled
ln -s ../conf-available/phpmyadmin.conf phpmyadmin.conf
```

- Symlink the configuration files for phpmyadmin in it's root folder:

```
cd /usr/share/phpmyadmin
ln -s /etc/phpmyadmin/config.inc.php config.inc.php
ln -s /etc/phpmyadmin/config.header.inc.php config.header.inc.php
ln -s /etc/phpmyadmin/config.footer.inc.php config.footer.inc.php
```

- Create a additional config file with the path to the **tmp** directory:

```
vim /etc/phpmyadmin/conf.d/tempdir.php
<?php
$cfg['TempDir'] = '/var/lib/phpmyadmin/tmp';
```

- Make sure the *phpmyadmin* user has been created in mysql:

```
mysql -u <my-admin-user> -p
SELECT user,host FROM mysql.user;
CREATE USER 'user'@'localhost' IDENTIFIED BY 'password';
GRANT USAGE ON phpmyadmin.* TO phpmyadmin
```

- The password is in file /etc/phpmyadmin/config-db.php. Restrict permissions of that file as it contains a password:

```
sudo chown root:www-data /etc/phpmyadmin/config-db.php
sudo chmod 640 /etc/phpmyadmin/config-db.php
```

- Create a regular MariaDB user for the purpose of managing databases through phpMyAdmin, as it's recommended that you log in using another account than the pma user. You could create a user that has privileges to all tables within the database, as well as the power to add, change, and remove user privileges, with this command. Whatever privileges you assign to this user, be

sure to give it a strong password as well:

```
sudo mariadb
GRANT ALL PRIVILEGES ON *.* TO 'user'@'localhost' IDENTIFIED BY
'password' WITH GRANT OPTION;
exit
```

- phpMyAdmin Configuration

Manual Upgrade on Debian 9

- Check latest version of phpMyAdmin
- Download and install

```
cd /usr/share/phpmyadmin/
sudo wget
https://files.phpmyadmin.net/phpMyAdmin/5.1.0/phpMyAdmin-5.1.0-english.
tar.gz
tar xzf phpMyAdmin-5.1.0-english.tar.gz
sudo mv phpMyAdmin-5.1.0-english phpmyadmin
```

- Modify the following lines in /usr/share/phpmyadmin/libraries/vendor_config.php

```
define('TEMP_DIR', '/var/lib/phpmyadmin/tmp/');
define('CONFIG_DIR', '/etc/phpmyadmin/');
```

- See How To Manually Upgrade phpMyAdmin and phpMyAdmin blowfish secret generator

Securing Your phpMyAdmin Instance

Edit /etc/apache2/conf-available/phpmyadmin.conf:

```
Alias /phpmyadmin /usr/share/phpmyadmin
<Directory /usr/share/phpmyadmin>
  Options FollowSymLinks
  DirectoryIndex index.php

  # Allow user to access without password
  Include conf-available/user-access.conf

  <IfModule mod_php5.c>
      <IfModule mod_mime.c>
          AddType application/x-httpd-php .php
      </IfModule>
      <FilesMatch ".+\.php$">
          SetHandler application/x-httpd-php
      </FilesMatch>

      php_flag magic_quotes_gpc Off
```

```
      php_flag track_vars On
      php_flag register_globals Off
      php_admin_flag allow_url_fopen Off
      php_value include_path .
      php_admin_value upload_tmp_dir /var/lib/phpmyadmin/tmp
      php_admin_value open_basedir
/usr/share/phpmyadmin/:/etc/phpmyadmin/:/var/lib/phpmyadmin/:/usr/share/php/
php-gettext/:/usr/share/javascript/:/usr/share/php/tcpdf/
  </IfModule>
</Directory>
```

conf-available/user-access.conf contains:

```
# Allow user to access without password
Require ip www.xx.yyy.zzz
```

Links

- How to Install phpMyAdmin on Debian 11 Bullseye (Apache)
- How to Install and Secure phpMyAdmin on Debian 11

From:
https://wiki.condrau.com/ - **Bernard's Wiki**

Permanent link:
https://wiki.condrau.com/deb11:phpmyadmin?rev=1664163059

Last update: **2022/09/26 10:30**