Configuration

Install Kubuntu. The following command adds Medibuntu's repository to Ubuntu. It also adds Medibuntu's GPG key to your keyring, which is needed to authenticate the Medibuntu packages.

```
wget --output-document=/etc/apt/sources.list.d/medibuntu.list
http://www.medibuntu.org/sources.list.d/$(lsb_release -cs).list
apt-get --quiet update
apt-get --yes --quiet --allow-unauthenticated install medibuntu-keyring
apt-get --quiet update
```

You may also wish to add the following packages. The first will cause many apps from the Medibuntu repository to appear in Ubuntu Software Center (Ubuntu 9.10+) or Add/Remove Applications (versions prior to 9.10). The second will allow users to generate crash reports against Medibuntu packages and submit them to the Medibuntu bugtracker.

```
apt-get --yes install app-install-data-medibuntu apport-hooks-medibuntu
```

Install individual packages

- With your favourite web browser, go to http://packages.medibuntu.org/.
- Choose the Ubuntu version you're currently using.
- Find the package for your architecture in the listing, and save it to your personal directory on your hard drive. You may need to also download any dependencies that are also in medibuntu.
- Right click on the package you just downloaded.
- Select Ubuntu Package Menu.
- Choose Install Package.

From:
http://wiki.condrau.com/ - **Bernard's Wiki**

Permanent link:
http://wiki.condrau.com/mserver9:config

Last update: **2009/12/25 20:40**