2025/11/06 18:31 1/3 Eclipse IDE

Eclipse IDE

The Eclipse IDE Integrated Development Environment is open source and provides an excellent environment to develop web applications. I migrated the LAMP server from XAMPP to WSL (Windows Subsystem for Linux) with the arrival of Windows 10. See here for XAMPP related instructions.

Application	Version
Eclipse for PHP Developers	2024-03
OS	Debian 12.5
Apache	2.4.59
PHP	8.3.7
MariaDB	10.11.6 ¹

¹MariaDB 10.11 versus MySQL 8.0

LAMP with Xdebug

Follow LAMP on Debian 12

Eclipse IDE

Java

Eclipse requires Java to run, so install this first.

- Install Java Runtime Environment 32 Bit Version or 64 Bit Version
- If you have recently installed Java 8 and uninstalled older versions, install Java SE Development Kit 8 and retry.
- If you get a Java was started but returned exit code=13 error, you most likely installed the wrong Java version. Try re-installing Java with the 64-bit version, or vice versa.

Eclipse

- Install Eclipse for PHP Developers
- Choose x:\ as installation path, where "x" can be any drive letter available to your system, also a portable one.
- How do I increase the heap size available to Eclipse?

JavaScript

Links

2025/11/06 18:31 2/3 Eclipse IDE

- JavaScript Editor Plugin for Eclipse
- Download Node.js
- How To Run / Debug Node.js Application With Eclipse

TypeScript

Install the TypeScript IDE for Eclipse.

- 1. Install required software: Java 7, Eclipse Kepler 4.3 or higher, Node.js.
- 2. In Eclipse go to Help → Install New Software...
- 3. Provide the installation location http://axmor.bitbucket.org/typecs/stable/update-site/
- 4. Mark the plugin version you would like to install then press **Next...**
- 5. On Install Details press Next...
- 6. Review and confirm the plugin to install.
- 7. Restart Eclipse.

Settings

- 1. Go to **Window** → **Preferences** → **General** and enable "Show heap status".
- 2. Go to **Window** → **Preferences** → **General** → **Workspace** and modify the Workspace settings.



3. Go to **Window** → **Preferences** → **General** → **Web browser** and set the desired browser for browser output.



4. Go to **Window** → **Preferences** → **PHP** → **Servers** and enter the web server settings.



5. Go to Window → Preferences → PHP → Validation and set the PHP version.



6. Go to **Window** → **Preferences** → **PHP** → **Debug** → **Debuggers** and check the XDebug settings. They must comply with the settings in the php.ini file. Set "Accept remote session (JIT)" to *off* if you don't want the debugger to automatically start when opening any URL on localhost.



7. There are three places where the "Break on first line" configuration can be set:

2025/11/06 18:31 3/3 Eclipse IDE

- Window → Preferences → PHP → Debug
- Project → Properties → PHP → Debug
- \circ Run \rightarrow Debug Configurations \rightarrow PHP Web Application \rightarrow <Your configuration> \rightarrow Debugger
- 8. Add or Edit **Debug Configurations...** If you pointed the DocumentRoot to your workspace, then you can leave the URL on "Auto Generate", otherwise you must modify the URL.



9. **Window -> Preferences -> PHP -> Code Style -> Formatter**. Select "PHP Conventions" as active profile.



- 10. If you have existing projects
 - o either select the project directory as workspace when first starting up the new eclipse, or
 - delete the workspace directories and files (filenames start with "."), then import the project directories with File -> Import -> General -> Existing Projects into Workspace

Links

- Adding existing project folders to the project explorer in eclipse
- Guide for installing Owncloud 9 to Synology NAS running DSM 6
- Install Owncloud 10 on DSM 6.1
- Setting Up a Programming Environment via Windows 10 Bash
- · eclipse stuck when building workspace

From:

https://wiki.condrau.com/ - Bernard's Wiki

Permanent link:

https://wiki.condrau.com/web:eclipse?rev=1716420475

Last update: 2024/05/23 06:27

