

# Windows Subsystem for Linux - Debian 10.3

## Cassandra, Hera, Vulcan, Hercules, Poseidon, Iapetus

### Installation

- Enable "Developer mode" in *Settings* -> *Update & Security* -> *For developers*
- Press Windows key + R and run **optionalfeatures.exe**. Enable *Windows Subsystem for Linux*. Restart the computer.
- Open Windows Power Shell as Administrator, then run the following line and reboot:

```
Enable-WindowsOptionalFeature -Online -FeatureName Microsoft-Windows-Subsystem-Linux
```

- Open the Microsoft Store and search for "Linux". Choose and get Debian, as per 2020-03-10 this is Debian 10 Buster.
- Open *Debian* from the start menu and complete installation.
- Upgrade all packages:

```
sudo apt update  
sudo apt upgrade
```

- Install packages:

```
sudo apt install vim  
sudo apt install wget  
sudo apt install zip  
sudo apt install rsync
```

- Create /run/sshd folder:

```
sudo mkdir /run/sshd
```

- Create a shortcut to the executable on your desktop:

```
C:\Users\user\AppData\Local\Microsoft\WindowsApps\debian.exe
```

- The root file system can be found at a path similar to:

```
C:\Users\bco\AppData\Local\Packages\TheDebianProject.DebianGNUlinux_76v4gfsz19hv4\LocalState\rootfs
```

- Add  and  icons to the shortcuts

### SSH Server

- Install packages:

```
sudo apt install openssh-server
```

- Follow the [SSH Client and Server](#) guide. SSH into your host and open port 22 in the Windows Firewall.

## Start SSH Server at Windows boot time

- Open a bash command shell and allow <user> to run ssh as root, add the following line after %sudo:

```
sudo visudo
%sudo ALL=(ALL:ALL) ALL
<user> ALL=(root:root) NOPASSWD: /etc/init.d/ssh
```

- Open Windows Task Scheduler and click *Create Basic Task...*
  1. General
    - Name : Start Bash SSH Server
    - Description: Start the WSL SSH Server via a bash command
    - Run only when user is logged on
    - Run with highest privileges
  2. Trigger
    - Begin the task: At log on [OR] On an event
    - (if you mount VeraCrypt volumes during boot it's better to use *On an event* and begin the task when the volumes are mounted)
    - Specific user: <user>
    - Enabled
  3. Actions
    - Action: Start a program
    - Program/script: C:\Windows\System32\bash.exe
    - Add arguments (optional): -c "/usr/bin/sudo /etc/init.d/ssh start"
  4. Conditions
    - Start the task only if the computer is on AC power
  5. Settings
    - *Uncheck* Stop the task if it runs longer than:
  6. Alternative Action when starting a non elevated script "startup"
    - Action: Start a program
    - Program/script: C:\Windows\System32\bash.exe
    - Add arguments (optional): -c "/home/user/startup"
    - Script "startup":

```
#!/bin/bash
sudo /etc/init.d/ssh start
```

## LAMP

- [LAMP on Debian 12 \(Apache 2.4, PHP 8.3, MariaDB 10.11\)](#)
- [Debian 9 - Apache 2.4 and PHP 7.4](#)
- [Debian 9 - MariaDB 10.3](#)

## Mounting encrypted drives

- WSL can mount encrypted drives, but they must be mounted at the time wsl or bash runs the first time after boot.
- If you do not execute any tasks when the host boots up, then just make sure your encrypted drives are mounted when you run wsl or bash.
- If you **do** execute WSL tasks when the host boots up, replace the *Task Scheduler* entry for the trigger and make it run after the *Mount* script has executed:

```
<QueryList>
  <Query Id="0" Path="Microsoft-Windows-TaskScheduler/Operational">
    <Select Path="Microsoft-Windows-TaskScheduler/Operational">*[EventData[@Name='TaskSuccessEvent']][Data[@Name='TaskName']='\Mount']]</Select>
  </Query>
</QueryList>
```

- Remember to “Enable All Task History” under Actions tab. **You might need to do this again after a Windows 10 major version upgrade.**

## Mounting external drives

```
mkdir /mnt/f
mount -t drvfs f: /mnt/f
```

## Links

- [Windows Subsystem for Linux Installation Guide for Windows 10](#)
- [How Does the Windows 10 Subsystem for Linux Work and What Is It For?](#)
- [Background Task Support in WSL](#)
- [SSH on Windows Subsystem for Linux \(WSL\)](#)
- [Backup with rsync on Windows \(WSL\)](#)
- [Docker Running Seamlessly in Windows Subsystem Linux](#)

From:

<https://wiki.condrau.com/> - **Bernard's Wiki**

Permanent link:

<https://wiki.condrau.com/win10:wsl>

Last update: **2024/04/25 16:40**

