

# Install MySQL database

## Installation

```
apt-get install apache2 php5-mysql libapache2-mod-php5 mysql-server
```

Assign a root password when asked for during the installation. When the installation is finished, restart the apache2 server:

```
/etc/init.d/apache2 restart
```

## Install phpMyAdmin

```
apt-get install phpmyadmin
```

1. Install your favourite distribution of phpMyAdmin in a directory you like. I installed mine at `/usr/share/phpMyAdmin`.
2. The privileges for the directory will be 755 with root user and group.
3. Go to `/etc/httpd/conf.d` directory and create a file with the name `phpMyAdmin.conf` (anything with the `.conf` extension will be parsed by Apache) and write a simple command: `Alias /phpMyAdmin /usr/share/phpMyAdmin`
4. Go to the directory you installed phpMyAdmin (`/usr/share/phpMyAdmin`), edit the `config.inc.php` file, and you are ready.
5. `$cfg['Servers'][$i]['controluser']` and `$cfg['Servers'][$i]['controlpass']` can be blank.
6. You or anybody can now login from ANY of your domains to phpMyAdmin, either as the root MySQL user (username: admin, password: the one you entered when you bought the server), or the specific user with privileges only to his own databases, entering: `www..com/phpMyAdmin`

## Restrict access to PhpMyAdmin to local network

Enter the following lines to `phpmyadmin.conf` in the `/etc/apache2/conf.d`

```
Order deny, allow
Deny from all
Allow from localhost 127.0.0.1 192.168.1.*
```

## add user and new database

with password:

```
shell> mysql -u root -p
```

without password:

```
shell> mysql -u root
mysql> SET PASSWORD FOR 'root'@'localhost' = PASSWORD('newpwd');
```

then:

```
mysql> CREATE USER 'user1'@'localhost' IDENTIFIED BY 'pass1';
mysql> CREATE database petstore;
mysql> SHOW databases;
mysql> USE database;
mysql> SHOW tables;
```

From:

<https://wiki.condrau.com/> - **Bernard's Wiki**

Permanent link:

<https://wiki.condrau.com/wserver:helsql>

Last update: **2010/03/30 14:42**

